SUBMITTAL SHEET

www.bisfitting.com
TEL: 714-288-2087 FAX: 714-288-2702

Job Name: **Contractor:**

Location: **Quantity:**

Engineer: **Date:**

Malleable Fittings

Features

* Brand: BIS
* UL Listed
* FM Approved
* 100% Tested Each Fitting
* Black or Hot-Dipped Galvanized
* Style: Banded
* Class 150



Specification

Material: Blackheart Malleable Cast Iron B300-06
Casting: Conform to ASTM A197
Hot-Dipped Galvanizing: Conform to ASTM A153
Max. Working Pressure: 300 PSI (Based on Sch 40 Pipes)
Fittings Dimension: Conform to ASME B16.3, B16.14, and B16.39
Thread Standard: NPT Conform to ASME B1.20.1
Tensile Strength: Min 43,000 PSI
Elongation: Min 6%
Hardness HB: Max 150

BIS PIPE FITTING INDUSTRY CO. product specifications and dimensions are approximate and are provided for reference only. It's the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of our products. BIS PIPE FITTING INDUSTRY CO. reserves the right to change or modify product design, construction, specification, model number or material without prior notice and without incurring any obligation to make such changes on BIS PIPE FITTING INDUSTRY CO. previously sold.