FPPI
An ASC Engineered Solution

Ball Drips, Brass

FPPI ball drips feature two piece brass construction. Their designed use is to prevent moisture accumulation on the "dry" side of fire department connections when used in conjunction with an approved check valve.

Part No.	Description	in	Pack Qty.
08-540-00	Ball Drip	½" IPS	10
08-541-00	Ball Drip	¾" IPS	10
08-542-00	Ball Drip	¼"x ½" NPT	10



085400 - 054100

Extension Nipples, Brass

Designed to be used to correct sprinkler head elevation without removing or re-cutting sprinkler drop. THIS PRODUCT IS COVERED BY ADDITIONAL DISCLAIMERS REGARDING SUITABILITY AND USE. PURCHASER AND USER TAKE FULL RESPONSIBILITY FOR THE USE OF THIS PRODUCT. FPPI WILL NOT BE HELD LIABLE FOR PRODUCT FAILURE OR DAMAGE CAUSED BY MISUSE. SEE INSTALLATION INSTRUCTIONS FOR DETAILS.

Part No.	Description	in	Pack Qty.
08-570-00	Takeout x ½" IPS Br. Spr. Ext.	½"	100
08-571-00	Takeout x ½" IPS Br. Spr. Ext.	¾"	35
08-572-00	Takeout x ½" IPS Br. Spr. Ext.	1"	35
08-573-00	Takeout x ½" IPS Br. Spr. Ext.	1½"	25
08-574-00	Takeout x ½" IPS Br. Spr. Ext.	2"	20
08-575-00	Takeout x ¾" IPS Br. Spr. Ext.	½"	25
08-576-00	Takeout x ¾" IPS Br. Spr. Ext.	¾"	25




08-570-00

Orifice Union

Orifice unions create a restricting orifice and are commonly used in pressure sensing lines or fire pump systems to provide adequate pressure drop.

Part No.	Description	in	Pack Qty.
08-537-00	Orifice Union	1" IPS x ½"	5
08-539-00	Orifice Union	½" IPS x 3/32"	10



08-539-00

Sight Glass, Brass

FPPI sight glasses feature brass construction with Lexan view windows for observation of flow. Typical use is for the sprinkler systems inspectors' test trim. Available in straight and restricted orifice patterns.

Part No.	Description	in	Pack Qty.
08-529-00	Sight Glass MxF	1" IPS	3
08-530-00	Sight Glass FxF ½" Orifice	1" IPS	5
08-531-00	Sight Glass MxF	1¼" IPS	4
08-532-00	Sight Glass FxF 17/32" Orifice	1" IPS	5
08-533-00	Sight Glass FxF	1½" IPS	1
08-535-00	Sight Glass FxF	2" IPS	1



08-530-00