Flush Mechanical Cleanout Repair Plug



83687



83687

- Holds up to 50 feet of back pressure
- Seals air tight! (Does not rely on threads to seal)
- Back pressure actually increases sealing ability
- Completely flush inside and out
- Can install cleanout cover over plug
- Cannot fall into the pipe
- Comes with 5/16" wrench
- Center is tapped for screw, and can be covered with cleanout cover
- Fits cleanouts only. Not designed to fit pipe.

PRODUCT	DESCRIPTION	MODEL	UNITS/CASE
83687	2" Flush Mechanical Cleanout Repair Plug	FCRP2	10
83688	3" Flush Mechanical Cleanout Repair Plug	FCRP3	10
83689	3-1/2" Flush Mechanical Cleanout Repair Plug	FCRP35	10
83690	4" Flush Mechanical Cleanout Repair Plug	FCRP4	10

T-Cone Combination Cleanout Test Plugs



86395

- Economical, rust-proof and reusable
- Positive sealing
- Tests up to 50 feet of head pressure

PRODUCT	DESCRIPTION	MODEL	UNITS/CASE
86375	Tests 1-1/2" Sch. 40 DWV	S152	50
86385	Tests 2" Sch. 40 DWV & Type "M" Copper Tube	S202	50
86390	Tests 3" Sch. 40 & Copper DWV; 2" Cast Iron Hub	S302	10
86455	Tests 3" Sch. 40 Socket	S300	50
86395	Tests 4" Type "M" Copper Tube, Cast Iron Closet Bend (SW), VCP Barrel	S401	50
86400	Tests 4" Sch. 40 & Copper DWV, PVC S&D, Cast Iron & VCP Barrel; 3" Cast Iron Hub	S402	10
86420	Tests 6" Copper DWV, PVC PSM (SDR 35), PVC DR-14, CI & VCP Barrel	S601	36
86425	Tests 6" Sch. 40 DWV, PVC DR-18, Cast Iron Barrel (EH)	S602	36
86435	Tests 8" Sch. 40 DWV, PVC PSM (SDR 35), PVC DR-18, VCP Barrel	S802	20