713™ CPVC Orange, Regular-Bodied, Fast-Setting



10126

- Regular-bodied, fast-setting, low-VOC CPVC cement for copper tube size and Schedule 40 pipe and fittings with interference fit through 2" (63 mm) diameter
- Specially formulated for plumbing applications
- For potable water to 180°F (82°C)

LISTINGS	PRODUCT	DESCRIPTION	MODEL	UNITS/CASE
UPC, NSF	10129	1/4 Pt. Can with Applicator Cap	107130651	24
	10128	1/2 Pt. Can with Applicator Cap	107130641	24
	10127	Pt. Can with Applicator Cap	107130631	12
	10126	Qt. Can with Applicator Cap	107130621	12

FlowGuard Gold® CPVC Yellow, Medium-Bodied, Fast-Setting



11026

- Regular-bodied, fast-setting, low-VOC CPVC cement for copper tube size and Schedule 40 pipe and fittings with interference fit through 2" (63 mm) diameter
- Specially formulated for plumbing applications
- For potable water to 180°F (82°C)

LISTINGS	PRODUCT	DESCRIPTION	MODEL	UNITS/CASE
UPC, NSF	11029	1/4 Pt. Can with Applicator Cap	127130851	24
	11028	1/2 Pt. Can with Applicator Cap	127130841	24
NSF	11027	Pt. Can with Applicator Cap	127130831	12
NSF	11026	Qt. Can with Applicator Cap	127130821	12
NSF	11025	Gal. Can with Screw-on Cap	127130811	6

FlowGuard Gold® is a registered trademark of The Lubrizol Corporation.