
Location: _____

MIFAB® F1100-C-W(D)

OVERFLOW DRAIN WITH STANDPIPE AND OPTIONAL DOME FOR MEMBRANE FLOOR AREAS

Specification: MIFAB® Series F1100-C-W(D) lacquered cast iron floor drain with anchor flange, cast iron membrane clamp ring with primary and secondary weepholes for waterproofing membrane, adjustable 4" (102) diameter ABS standpipe and stainless steel dome. (For non-membrane floors, use MIFAB F1100-W(D) Series.)

Function: Used in an overflow drain in decorative fountains, pools, fish ponds and other similar areas. The dome assembled to the top of the standpipe prevents floating debris from entering the drain line. Membrane clamp is provided to secure the waterproofing membrane.



Metric equivalents see chart below. (Dimension) Denotes Millimetres

PARTS:


A1 BODY


A1-W

OR


A1-WD


A1-C1


HS-1

F1100-C-W(D) Series meets ANSI-ASME floor drain standard A112.6.3-2001

PIPE SIZE	BODY HEIGHT				
	NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC/ABS (-30)/(-31)
2" (51) ○	3" (76) ☐	3 3/8" (86) ☐	2 1/4" (57) ☐	3 3/4" (95) ☐	2 15/16" (75) ☐
3" (76) ○	3" (76) ☐	3 3/8" (86) ☐	2 5/8" (67) ☐	3 3/4" (95) ☐	3 3/4" (95) ☐
4" (102) ○	3" (76) ☐	3 3/8" (86) ☐	2 5/8" (67) ☐	3 3/4" (95) ☐	3 3/4" (95) ☐
5" (127) ○	3" (76) ☐	--	2 5/8" (67) ☐	3 3/4" (95) ☐	--
6" (152) ○	3 1/4" (83) ☐	6 1/2" (165) ☐	--	--	--

SUFFIX	OPTIONAL VARIATIONS
☐ -6	Security screws (T-20 Torx & pin)
☐ -7	1/2" trap seal primer connection
☐ -8	Backwater valve (2", 3", 4")
☐ -11	Acid resistant epoxy coated body
☐ -13	Galvanized body
☐ -15	Extension
☐ -21	Secondary flat stainless steel strainer (2", 3", 4")
☐ -28	Stainless steel body (Type 304)
☐ -30	PVC socket connection body
☐ -31	ABS socket connection body
☐ -34	Closure plug
☐ -40	Underdeck clamp
☐ -41	Sump receiver

SUFFIX	OPTIONAL VARIATIONS
☐ -90	Threaded side outlet (2", 3", 4") (cast iron only)
☐ -90NH	No hub side outlet (2", 3", 4") (cast iron only)
☐ -95	Client logo
☐ -BA	Minimum 51% material cost made in the USA
☐ -C2	High rough-in membrane clamp (min. 1 9/16" (40))
☐ (Standard)	No hub outlet
☐ -MG	MI-GARD Floor Drain Trap Sealer (2", 3" or 4")
☐ P	Push on outlet
☐ -PSA	Pennsylvania Steel Act compliant product
☐ T	Threaded outlet (2", 3", 4")
☐ X	Inside caulk outlet
☐ -Z	Extended wide elastomeric flange

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____ Page No: _____

Section No: _____ Contractor: _____

Schedule No: _____ Purchase Order No: _____

MIFAB *reserves the right to make changes in material and design without formal notice and obligation.*

USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880