SUBMITTAL SHEET

www.mspipe.kr

Job Name: Contractor:

Location: Quantity:

Engineer: Date:

Steel Pipe SCH 10

Features



* Manufactured According to ASTM A53 and A135
* Sch 10, ERW, Grade A, Type E
* Meets NFPA 13
* Plain Ends or Grooved Ends
* Corrosion Resistant Surface
* Mill Lacquer Coated
* UL List & FM Approved

Chemical Requirement (Max. %)

C	Mn	P	S	Others
0.25	0.95	0.05	0.045	Note 1

Note 1: Residual Elements Cu (0.4), Ni (0.4), Cr (0.4), Mo (0.15), and V (0.08) Combined Shall Not Exceed 1%.

Tensile Strength (Min. Psi)

Yield	Tensile
30,000	48,000

Specification

Pipe Mill: MS Pipe
Country of Origin: South Korea
Nominal Pipe Size: 1-1/4" to 4"
Length: 21 Feet

Size	O.D.	I.D.	Empty Lbs/Ft	WFW* Lbs/Ft	Pcs/Lft
1-1/4"	1.660"	1.442"	1.810	2.548	61
1-1/2"	1.900"	1.682"	2.090	3.095	61
2"	2.375"	2.157"	2.640	4.298	37
2-1/2"	2.875"	2.635"	3.530	6.008	30
3"	3.500"	3.260"	4.340	8.122	19
4"	4.500"	4.260"	5.620	12.084	19

*WFW=Water Filled Weight

UL LISTED

FM APPROVED

MS Pipe product specifications and dimensions are approximate and are provided for reference only. It's the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of our products. MS Pipe reserves the right to change or modify product design, construction, specification, model number or material without prior notice and without incurring any obligation to make such changes on MS Pipe previously sold.